## IP CAMERA COMPARISON CHART














Levels		VALUE EXPRESS		VALUE	PERFORMANCE	PROFESSIONAL
		Entry-level Budget Cameras	A Step Up without Stretching the Budget	Best Low Light Color Image	All-in-One Security Defense Solution	Hikvision's Most Powerful and Versatile Camera
Key Features Series		Uses the Latest Video Compression (H.265+)     Fixed and Varifocal Lenses     Exclusive US model Numbers     Matching 4- and 8-channel NVRs	Multiple Resolutions Available     Multiple Lens Sizes, includes Varifocal	24/7 Color Imaging Technology     Advanced Sensor & Super Aperture f1.0     G2 Models Support 2nd Generation AcuSense     Integrated Supplemental White Light     Integrates Well with Pro and Plug and Play NVRs	2 nd Generation AcuSense Technology     Human and Vehicle False Alarm Filtering     Strobe Light & Audio Active Deterrent     Fully Compatible w/ Pro and Plug and Play NVRs     Exclusive US Model Numbers	Most Advanced Deep Learning Algorithms     Light finder, EXIR 2.0     6-in-1 Switchable Algorithms     Filter out more than 95% false alarm     Classify target objects & attribute search     Area density control.
		ECI	2xx3	ColorVu 2xx7	2nd Gen AcuSense PCI	2nd Gen DeepinView iDS 7 Series
Image Quality		2 MP: 0.028 Lux, Digital WDR 4 MP: 0.018 Lux, 120 dB True WDR	2 MP: 0.028 Lux 4 MP: 0.018 Lux 6/8 MP: 0.028 Lux 120 dB True WDR	4 MP: 0.0014 Lux 8 MP: 0.0005 Lux 120dB(G1) / 130 dB(G2) True WDR	2 MP: 0.002 Lux 5 MP: 0.003 Lux 8 MP: 0.003 Lux Powered by DarkFighter, 120 dB True WDR	4 MP: Color: 0.001 Lux 12 MP: Color: 0.009 Lux 4 MP: 140 dB True WDR DarkFighter Technology
Max Resolution		4 MP	8 MP	8 MP	8 MP	12 MP
Codec		H.265+	H.265+	H.265+	H.265+	H.265+
Video Content Analysis	Motion Detection	√	√	√	√	✓
	Line Crossing		√	√	√	√
	Intrusion		√	√	√	✓
	Object Removal			√ (G1 only)	√	√
	Unattended Baggage			√ (G1 only)	√	✓
	Region Entrance Detection			√ · · · · · · · · · · · · · · · · · · ·	√	√
	Region Exiting Detection			√	√	✓
	Scene Change			√	√	√
	Audio Exception				√	<b>√</b>
	Defocus					√
	Face Detection	√	√	√	Advanced Face Capture	Human & Vehicle Recognition Attribute Classification
	Human/Vehicle Detection			Advanced (G2 only)	Advanced	Human & Vehicle Attribute Search
	People Counting					√
	Hard Hat Detection					√
	Queue Management					√
Build-in Audio Alarm & Strobe Light					√ (SL model)	
Multiple Streams		2	3	3	4	10
Max Frame Rate		30 fps	30 fps	30 fps	2 MP @ 60 fps	2 MP @ 60 fps
EXIR 2.0 Range Max (meters) / Supplement Light		30	30 / 50 (Long Bullet/VF)	30 / 40 (White Light)	40 / 60 (VF)	30 / 50 / 100
Power Output for PIR, Sensors, Microphones					12V DC, 0.1A (Fix lens, non-SL models)	12V DC, 0.2A (Indoor & -Y models only)
Electric Image Stablization/ Defog						√
Anti-Corrosion Coating						√ (-Y mondels only)
Temperature Range		-30° C to 50° C (-22° F to 122° F)	-30° C to 60° C (-22° F to 140° F)	-30° C to 60° C (-22° F to 140° F)	-30° C to 60° C (-22° F to 140° F)	-40° C to 60° C (-40° F to 140° F) Outdoor models with heaters (-H) only

©2021 Hikvision USA Inc. and Hikvision Canada Inc. All rights reserved. Hikvision is a registered trademark of Hikvision Digital Technology Co., Ltd. in the US, Canada and other countries. Product specifications and availability are subject to change without notice.





## PERFORMANCE