

Safer Hospitals with Instant, Accurate Temperature Screening Solutions

Temperature Screening: One of the CDC's Recommendations for Reopening Business

Hospitals face new challenges these days. With an uptick in patients and a heightened responsibility to ensure the safety of staff and patients, advanced temperature screening can help.

Easy-to-operate Hikvision temperature detection cameras can facilitate safe operations and advanced screening for hospitals, dental offices and other healthcare facilities. Thermal cameras can help you easily and quickly pre-screen staff, patients, and visitors before they enter the hospital. Pre-screening takes less than one second, is highly accurate, and it offers contactless measurement from a distance. And, our rapid deployment solutions can be installed quickly and easily.



Extremely Safe-Contactless Measurement from a Distance



Instant One-Second Screening



Smart-Only Screens **Human Skin Surface**



Accurate up to ± 0.5 Degrees Fahrenheit with Blackbody Calibrator



Flexible, No-Wire for Simple installation

Application Scenarios



Bi-Spectrum Live View:

- · In addition to rapid and effective temperature measurement, Hikvision's bi-spectrum camera models combine thermal and optical imaging for excellent visual quality and identification capabilities.
- · Ease of installation with Hikvision's tripod mounting, simple wiring system, and rapid deployment solution.

Mask Detection and User-Friendly Display Interface:

- · All-in-one solution uses Hikvision's DeepinMind NVR, and provides these added features:
 - · Mask Detection
 - · Screening Results are Easy to Understand on User-Friendly Display Interface
 - · Search by Picture



DeepinView NVR

iDS-9632NXI-I8/X(B)




· 32-Library Capacity Up To 100,000 Face Images, Face Mask Detection Support

· Identity Verification & Stranger Alarm

Wireless Temperature Screening:

- · Hikvision's handheld thermographic cameras can be used for indoor entry/exit points all throughout the facility.
- Handheld thermal cameras are accurate up to ±0.9 degrees Fahrenheit, at a distance of 3.3 to 6.6 feet.
- Use our Hik-Thermal app for real-time viewing, reports, and temperature measurement.








HikCentral Professional CMS _

HikCentral Professional, Hikvision's central management system (CMS) is a powerful, flexible, and efficient software to manage all cameras using server-client architecture. Hospitals and other healthcare facilities can use HikCentral Professional for live viewing and long-term storage of video for record-keeping, safety, and to comply with regulations.


HikCentral Professional also provides:

- · Local monitoring, instant alarm pop-ups, and temperature measurement reports
- · Identity information registered when elevated skin-surface temperature is detected
- · Data can be intuitively searched, displayed and easily exported

Personnel Access Management & Skin-Temperature Measurement



Real-Time Pop-Up Alarm



Dashboard



Product Showcase

Thermographic Bullet Camera DS-2TD2617B-6PA

Optical: 2688x1520

- Thermal: 160x120,
- 3 mm / 6 mm lens · Accuracy of ±0.9° F
- (±0.5° F with Blackbody Calibrator)
- Effective Range of 4.9 to 9.8 ft.
- Skin-Surface Temperature up to 30 People at a Time
- Face Mask Detection

Blackbody Calibrator



- Accuracy of ±0.5° F
- Temperature Stability: ±32° F
- Effective Emissivity: 0.97 ± .02

Thermographic Turret Camera


DS-2TD1217B-3PA

- Optical: 2688x1520
- Thermal: 160x120, 3 mm / 6 mm lens
- Accuracy of ±0.9° F
- (±0.5° F with Blackbody Calibrator)
- Effective Range of 2.6 to 4.9 ft. Skin-Surface Temperature up to 30 People
- at a Time
- · Face Mask Detection

DeepinView NVR



- 16-Channel Face Picture Comparison Support 32-Library Capacity Up To 100,000 Face Images,
- Face Mask Detection Support
- · Identity Verification & Stranger Alarm



Thermographic Handheld Camera DS-2TP21B-6AVF/W

- Thermal Resolution: 160x120 Optical Resolution: 640x480
- · Wi-Fi Supported
- Accuracy of ±0.9° F
- Effective Range of 3.3 to 6.6 ft.
- 3.5-Inch LCD Touch Screen
- Quick Non-Contact Rapid Deployment with Tripod

HikCentral Professional CMS

- · Local Monitoring
- · Instant Alarm Pop-ups
- · Temperature Measurement Alarm Reports
- · Quick Record Search and Export



SCAN BELOW



